

PER LAVORAZIONI INTERNE
AL FORO Ø65 MINIMO

For machining internal
holes with Ø65 min. hole

Fuer interne Bearbeitungen
am loch minimum Ø65

Cod. MT	Cod. OKUMA	Mandrino Spindle Spindel	I	RPM	Lubrificazione int. Coolant through Innenkuehlung	Lubrificazione est. Ext. coolant Aussenkuehlung	B	Tipo Macchine Machine type Maschinen typ	CHIAVI INCLUSE Keys included Schluessel einbegriffen	
1270KU_R10_40B00	-	CHG	1:1	4000		X	93	LB15/300 LT15 LR15 LU15M	CHUB13	CHUB10
1270KU_R10_40B01	-	CHG	1:1	4000		X	101	LB25/400 LR25	CHUB13	CHUB10


OKUMA

MOD: LB15/300 LT15 LR15 LU15M - LB25/400 LR25

MODULO MOTORIZZATO RADIALE VD140 INT. 150 mm

Radial driven tool VD140 150 mm interaxis

Radial angetr. Werkzeug VD140 Int. 150 mm



M.T. srl

Via dei Tamerici 1/3
Tel. 0541/956034-957884

Fax 0541/956341

47842 S. GIOVANNI IN M. (RN)

e-mail: mima@mtmarchetti.com

http://www.mtmarchetti.com

PRODUZIONE MODULI ROTANTI



PAGINA OKU125-2-00